



ANTHONY
LIFTGATES, INC.®

Medium RailTrac™

1-800-482-0003

www.anthonyliftgates.com

AR Series:
1,200, 1,800, 2,500



AR
High Cycle: 3,000



PCR Series:
1,800, 2,500



PCR
Gas Bottle



Anthony Medium RailTracs

replace these
competitor
models:

MAXON:
RCM-12,
RCM-16
RC-2, RC-3,
RC-4, RC-5,
RC-6
RCM-CS-16

WALTCO:
MDR-125,
MDR-160

The Anthony Difference

4 Reasons Why We Are The Lowest Cost of Ownership!

1. Lifetime Warranted Slide Runners - We designed our slide runners to keep on working, day after day, year after year - an Anthony Exclusive! We use one-piece aluminum extrusions for superior performance with no plastic inserts to wear and replace. Dissimilar metal slide channels (aluminum and steel) reduce friction and extend service life.

2. Service-Free™ Bushings - We use service-free bushings at all sprocket locations to ensure smooth operation and extend the service life, while eliminating the need for routine lubrication.

3. Roller Chain Drive - We use heavy-duty roller chains for long life and greater reliability, no cables like some of our competitors use.

4. Power Open / Power Close - We offer effortless OPEN-CLOSE non-hydraulic operation. The platform automatically locks for travel in the stored position when it's raised in one convenient operation. Ease of operation means less operator fatigue which can lead to greater productivity

The Anthony Difference

- 1. Steel Power Unit Enclosure** – won't crack or break in cold weather like plastic units used by some of our competitors.
- 2. Steel platforms and weldments** are prepped to a near white finish with a shot-blast process, then the parts are powder-coat painted and cured at 400 degrees F for 30 minutes to ensure the best possible appearance, impact resistance, coating adhesion, and wear resistance.
- 3. Low operation pressure** extends the life of the power unit, hoses, cylinder seals, and battery.
- 4. Large-Bore Double-Weight Hydraulic Cylinder** – Our oversized cylinder allows the hydraulic system to operate at a lower pressure, increasing the service life of all hydraulic components.

Each Anthony Medium RailTrac liftgate is factory assembled, energized, completely cycled on our test stand, pressure set, oil filled, all to ensure the highest quality when it reaches the end user.

- 5. Zero leak SAE connections**, an Anthony pioneered feature. No leak-prone pipe threads are ever used.
- 6. Potted Switches** – All Anthony switches are "potted" to seal out moisture. The terminals and connections are permanently separated and sealed in epoxy to eliminate corrosion and electrical failure.
- 7. Positive Electrical Connections** – Heat-shrink silicone wire terminals insulate electrical connections to seal out moisture. Anti-rotational terminals insure rugged circuit protection.
- 8. E-Z Mount Installation** – All Anthony liftgates are shipped pre-assembled for fast, clean, easy installation.
- 9. Factory Installed Hydraulic Fluid** – Factory filling helps prevent contamination during installation. Our standard is Mobil Multi-Purpose ATF. For cold weather applications we use Mobil 1 Synthetic ATF.

All Anthony Medium RailTrac liftgates are serial numbered and computer logged for quick factory service identification, warranty and repair information.

ANTHONY
LIFTGATES, INC.®