



**ANTHONY**  
LIFTGATES, INC.®

# LoadBlazer™ Series

1-800-482-0003  
www.anthonyliftgates.com

**ALB-1500**



**ALB-1500A**



## Anthony LoadBlazers

replace these competitor models:

MAXON:  
Mighty Mmax  
1300 series

Del/Ultron:  
PTN series

Tommy Gate:  
G2 dual drive  
series

Eagle Lift:  
EDL-60,  
EDL-58,  
EDL-64

## The Anthony Difference

### 5 Reasons Why Our Pickup Liftgates Offer A New Dimension!



- 1. Direct Drive Twin Cylinder Power** – We provide even, hydraulic lifting power at each side of the platform, and there are no lifting cables or chains to maintain and wear out.
- 2. Heavy-Duty Stabilizer Beam** – Our beefy 3 inch, 11 gauge tubular steel beam connects the two lift arms, balancing heavy loads and virtually eliminating any side-to-side shifting.
- 3. 1,500 Pound Lifting Capacity** – The LoadBlazer has the power to easily load most pickups to their *rated capacity* in just one lift.
- 4. Large Platform** – We offer a large 50" x 41" + 6" platform with a full 52.5" opening into the truck bed and a bed height up to 46". A two-piece diamond treadplate steel platform folds evenly with the sides of the truck bed in the closed position allowing normal rear visibility. (aluminum platform model available)
- 5. Premium Appearance** – A brushed aluminum appearance plate covers the platform bolsters and provides a smooth, clean, OEM truck look.

## ***The Anthony Difference***

- 1. Easy Access Power Unit – Accessible through a steel panel on top of the rear bumper housing. A clear-view hydraulic reservoir provides quick fluid level inspection.**
- 2. Steel platforms and weldments are prepped to a near white finish with a shot-blast process, then the parts are powder-coat painted and cured at 400 degrees F for 30 minutes to ensure the best possible appearance, impact resistance, coating adhesion, and wear resistance.**
- 3. Low operating hydraulic pressure extends the life of the power unit, hoses, cylinder seals, and battery.**
- 4. Zero leak SAE connections, an Anthony pioneered feature. No leak-prone pipe threads are ever used.**
- 5. Service-Free™ – Composite bushings are used at all pivot points to prevent wear to pins and arms. No lubrication is required.**

***Each Anthony LoadBlazer liftgate is factory assembled, energized, completely cycled on our test stand, pressure set, oil filled, all to ensure the highest quality when it reaches the end user.***

- 6. Potted Switches – All Anthony switches are “potted” to seal out moisture. The terminals and connections are permanently separated and sealed in epoxy to eliminate corrosion and electrical failure.**
- 7. Positive Electrical Connections – Heat-shrink silicone wire terminals insulate electrical connections to seal out moisture. Anti-rotational terminals insure rugged circuit protection.**
- 8. E-Z Mount Installation – All Anthony liftgates are shipped pre-assembled for fast, clean, easy installation.**
- 9. Factory Installed Hydraulic Fluid – Factory filling helps prevent contamination during installation. Our standard is Mobil Multi-Purpose ATF. For cold weather applications we use Mobil 1 Synthetic ATF.**
- 10. Fits Full-Sized Pickups – The LoadBlazer fits most full size GM, Ford, and Dodge pickups.**
- 11. Utility Body Application - A special mounting kit easily adapts the LoadBlazer to fit most service bodies.**
- 12. Spare Tire Access – Easy accessibility is through two holes in the rear frame.**

***All Anthony LoadBlazer liftgates are serial numbered and computer logged for quick factory service identification, warranty and repair information.***